

E1U-2LRV(2.8) AI Lite

**2MP Dual Light Bullet Camera
with Microphone**



Features

- 1/3" CMOS Sensor
- Support H.264/H.265/H.265+
- Support ONVIF Profiles
- Ingress Protection: IP67
- 2 White Lights and 2 IR Lights
- Support DWDR, 3D Noise Reduction, Backlight Compensation, and White Balance, Suitable for Different Monitoring Environments
- Support Remote Monitoring via Mobile App
- Built-In Microphone
- With 0.5T Computing Power



Technical Specifications

HOOOWITS

Model E1U-2LRV(2.8) AI Lite

Major Specifications

Camera

Image Sensor	1/ 3" CMOS
Maximum Resolution	1920 (H) × 1080 (V)
Video Compression Standard	H.264/H.265/H.265+
Video Frame Rate	Main Stream: 1920*1080@(1-25/30 fps) Sub stream:448P(800*448)/D1(704*576)/360P(640*360)/ CIF(352*288)@(1-30 fps)
Streaming Capability	Dual Stream
Bit Rate Control	Support VBR, CBR
Focal Length	2.8mm
Max Aperture	F2.0
Lens Aperture Type	Fixed Iris
Angle of View	H:100.5° , V:55.9° , D:116.9°
White Light Range	20m
White Light	2
IR Range	30m
Infrared light	2
Minimum illumination	0.02lux@F2.0

Function

Motion Detection	Support
Email Alert	Not Support
Image Rotation	Support
Wide Dynamic	DWDR
SD card	Not Support
External Audio Input	Not Support
Ethernet	10M/100M Ethernet, RJ45 port
Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
Client	HOLOZ VMS, HOLOZ App
WEB Interface	Support English/Chinese/Russian/Japanese/Korean/Italiano/Português etc.

Network

Intrusion Detection	Support
Tripwire Detection	Support
Off-duty Detection	Support
Passenger Flow Statistics	Support

Intelligent

General Specifications

Power type	PoE 48V, 0.2A (IEEE 802.3af)
Power consumption	Day ≤3W Night ≤7W
Operating temperature	-30°C to +60°C
Operating humidity	10% to 90% (Non-Condensing)
IP rating	IP67
Weight	330g (0.73lb)
Weight (With Package)	380g (0.84lb)
Dimension	179mm*67.2mm*62.5mm (L*W*H)
Dimension (With Package)	180mm*70mm*70mm (L*W*H)

Dimensions

